



X TAB 1.0 Android tablet ATEX zones 2/22

Protection mode:

Type of protection: II 3G Ex ic IIC T4 Gc
II 3D Ex ic IIIB T135°C Dc IP54

Class of temperature: T4
Zones : 2-22

Description:

The X.TAB 1.0 is the first tablet among industrial products. Waterproof and dustproof, with a large memory and a powerful battery.

Supply with:

- Lithium ion battery 7000 mAh
- Wall charger USB
- USB cable
- Quick start manual and safety instructions
- Display cleaning towel.

(Display protection foil on request.)



Technical data:

Type	X.TAB 1.0
Operating System	Android 4.1.2
Microsoft Exchange Server	Compatible
Lone Worker Protection	optional
Size	213 x 140 x 20 mm weight: 650 g weight: 650 g
Processor	qualcomm MSM8225Q (quadcore 1.2 GHz)
Protection type	IP 67
PTT	Push to Talk (server based), optional
Network	WCDMA (850/1900/2100 MHz), GSM (850/900/1800/1900 MHz)
Wi-Fi®	802.11b/g/n, 13 channels (all)
Bluetooth	V2.1, EDR class 2
NFC	Near Field Communication
Communication	SMS, MMS, E-Mail (POP3, IMAP, Microsoft™ Exchange)
Display	7" HVGA (800 x 1280 IPS) with capacitive touchscreen
Memory	1GB DDR2 memory 16GB ROM
Micro-SD	up to 32GB
Camera	8MP rear camera 2MP front camera
Location	GPS, AGPS Support
Sensors	G-Sensor
Battery	7000mAh Lithium ion battery
Standby	up to 450 hrs.